



BAC1205N

BAC1205N/2403N battery charger, adopts the latest switch power components, is specially designed for charging lead-acid starting battery according to its property. This charger is suitable for lead-acid battery long-term supplementary charge (float charge).

Product Code : 6070023
Power Supply : AC(100~277)V
Case Dimensions : 95*149*61(mm)
Operating Temp. : (-30~+55)°C
Weight : 0.45kg

COMPLETE DESCRIPTION

BAC1205N/2403N battery charger, adopts the latest switch power components, is specially designed for charging lead-acid starting battery according to its property. This charger is suitable for lead-acid battery long-term supplementary charge (float charge).

PERFORMANCE AND CHARACTERISTICS

Product with the following characteristics,

1. Designed in switching power structure, wide range of AC voltage input, small volume, light weight and high efficiency;
2. Two-stage charging method (constant current firstly and then constant voltage), fully considering charging property of the lead-acid battery, can avoid overcharging and extent extend the battery life to the fullest;
3. With short circuit and reverse connection protection;
4. Suitable for charging 12V or 24V batteries with corresponding model BAC1205N or BAC2403N;
5. LED display: charging indication and full charged indication;
6. Easy installation: guide-rail way installation, screw mounting installation;
7. Built-in terminals, flame retardant plastic shell.