



## HMC4000RM

HMC4000RM remote monitoring controller integrates digitization, intelligentization and network technology which are used for remote monitoring system of single unit to achieve remote start/stop functions. It fit with LCD display, and optional Chinese/English languages interface. It is reliable and easy to use.

Product Code : 6030038

Power Supply : DC(8~35)V

Case Dimensions : 135\*110\*44(mm)

Operating Temp. : (-25~+70)°C

Weight : 0.22kg

## **COMPLETE DESCRIPTION**

HMC4000RM remote monitoring controller integrates digitization, intelligentization and network technology which are used for remote monitoring system of single unit to achieve remote start/stop functions. It fit with LCD display, and optional Chinese/English languages interface. It is reliable and easy to use.

## **PERFORMANCE AND CHARACTERISTICS**

1. 132\*64 LCD with backlit, optional Chinese/English interface display, and push-button operation;
2. Hard-screen acrylic material been used to protect screen with great wear-resisting and scratch-resisting functions;
3. Silicone panel and buttons with great performance to work in high/low temperature ambient;
4. Connect to host controller via RS485 port to achieve remote start/stop control in remote control mode;
5. With LCD brilliance level (5 levels) adjusting button, it is convenient to use in different occasion;
6. Waterproof security level IP65 due to rubber seal installed between the controller enclosure and panel fascia.
7. Metal fixing clips are used;
8. Modular design, self extinguishing ABS plastic enclosure and embedded installation way; small size and compact structure with easy mounting.