



## SGPT110-04

SGPT110-0.4 piezoresistive pressure transmitter is based on MEAS original advanced highly stable silicon piezoresistance transmitter, which is installed into a 304 stainless steel enclosure. With premium performance of compatibility, stability, reliability and accuracy, SGPT110 can be widely used for gas and liquid (compatible with stainless steel 304) pressure measurement.

Product Code : 6030035

Power Supply : DC (12~36)V (DC 24V)

Operating Temp. : (-40~+125)°C

Weight : 0.12kg

## **COMPLETE DESCRIPTION**

### **OVERVIEW**

SGPT110-0.4 piezoresistive pressure transmitter is based on MEAS original advanced highly stable silicon piezoresistance transmitter, which is installed into a 304 stainless steel enclosure. With premium performance of compatibility, stability, reliability and accuracy, SGPT110 can be widely used for gas and liquid ( compatible with stainless steel 304) pressure measurement.

### **PERFORMANCE AND CHARACTERISTICS**

1. Measuring range: (0~0.4)MPa
2. Two-wire standard output: 4 mA ~20 mA
3. Wide working temperature range: (-40°C~125°C), with temperature compensation and common mode rejection functions.
4. Whole stainless steel structure
5. O-shape gasket
6. Pluggable connection, small volume, and low power consumption.